



R Series ---Thermal Fuse

Safety Electronics Technology

Features:


- Suitability of automatic soldering process
- No Contact Resistance
- Accuracy of cutoff temperature
- Rapid and reliable fusing action

Applications:

- Motor
- Transformer
- Protection of MOV
- Capacitor
- Lithium Battery
- Power Surge Strip
- House Appliance



A	B	C	D	E
14.0±0.5mm	38±5mm	4.0±0.5mm	4.5 or below mm	1.05±0.05mm



Model No.	Tf (°C)	Fuse-Temp (°C)	Th (°C)	Tm (°C)	Ir (A)	Ir (V)	RoHS
R1	102	98±2	72	200	15	250(AC)	▲
R2	115	111±2	85	200	15	250(AC)	▲
R3	125	121±2	95	200	15	250(AC)	▲
R4	130	125±2	100	200	15	250(AC)	▲
R5	135	130±2	105	200	15	250(AC)	▲
R6	145	140±2	115	200	15	250(AC)	▲
R7	150	145±2	120	200	15	250(AC)	▲
R8	133	130±2	105	200	15	250(AC)	▲
R9	136	131±2	106	200	15	250(AC)	▲
R10	117	113±2	87	200	15	250(AC)	▲
R11	127	123±2	97	200	15	250(AC)	▲
R12	103	98±2	72	200	15	250(AC)	
R13	139	135±2	110	200	15	250(AC)	▲
R14	140	135±2	110	200	15	250(AC)	▲
R15	169	165±2	139	200	15	250(AC)	
R16	160	154±2	130	200	15	250(AC)	▲
R17	187	182±2	157	200	15	250(AC)	
R18	86	81±2	51	200	15	250(AC)	▲
R19	85	81±2	55	200	15	250(AC)	▲
R20	92	92±2	62	200	15	250(AC)	▲
R21	97	93±2	70	200	15	250(AC)	▲
R22	93	93±2	66	200	15	250(AC)	▲
R23	90	85±2	58	200	15	250(AC)	
R24	100	95±2	72	200	15	250(AC)	
R25	120	115±2	90	200	15	250(AC)	▲
R26	95	91±2	65	200	15	250(AC)	▲

● Approved ○ Under application ▲ RoHS compliance

* Xiamen SET Electronics Co., Ltd reserves the right to modify the characteristics published in this leaflet.