


## Features

- 3-electrode arrester
- Very small size
- Extremely fast response time
- Stable performance over life
- Extremely low capacitance (<1.5pF)
- High insulation resistance



## Applications

- Line protection
- Station protection
- Base stations

## Electrical specifications

DC spark-over voltage <sup>1) 2) 4)</sup>	600 ± 20	V %
Impulse spark-over voltage <sup>4)</sup>		
at 100 V/μs - typical values of distribution	< 800	V
at 1 kV/μs - typical values of distribution	< 900	V
Service life <sup>3)</sup>		
5 operations    50 Hz, 1 s	10	A
10 operations    8/20 μs	10	kA
300 operations    10/1000 μs	200	A
Insulation resistance at 100 VDC <sup>4)</sup>	> 1	GΩ
Capacitance at 1 MHz <sup>4)</sup>	< 1.5	pF
Transverse delay time	< 0.2	μs
Arc voltage at 1 A	~ 35	V
Glow to arc transition current	~ 1	A
Glow voltage	~ 200	V
Weight	~ 2.5	g
Operation and storage temperature	-40 ~ +90	°C
Climatic category (IEC 60068-1)	40/ 90/ 21	
Marking, blue negative		

1) At delivery AQL 0.65 level II, DIN ISO 2859.


2) In ionized mode.

3) Tests according to ITU-T Rec. K. 12 and UL 497B.

4) Tip or ring electrode to center electrode.

Terms and current waveforms in accordance with: ITU-T Rec. K.12; IEC 61643-21 and DIN 57845/VDE0845.

## Dimensional drawing




## Cautions and warnings

- Surge arresters must not be operated directly in power supply networks.
- Surge arresters may become hot in case of longer periods of current stress (danger of burning).
- Surge arresters may be used only within their specified values. In case of overload, the headcontacts may fail or the component may be destroyed.
- Damaged surge arresters must not be re-used.

## Part Numbering System

**GDT RF 3R D7-600**



## Package Information

Quantity: 100PCS(Plastic box), 5000PCS(Carton).

Measurement: 197 × 167 × 9mm(Plastic box), 360 × 260 × 210mm(Carton).

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

Caution: Operation beyond the rated voltage or current may result in rupture electrical arcing or flame.

## CONTACT INFORMATION

**SHANGHAI CHANGYUAN WAYON CIRCUIT PROTECTION CO., LTD.**

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201202

Tel: 86-21-50310888 Fax: 86-21-50757680 Email: [market@way-on.com](mailto:market@way-on.com)

WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.